

Yealink

WH64 BASE



DUAL CONNECTIVITY WITH DECT BASE



Combining cutting-edge technology with exceptional comfort, the **Yealink WH64** offers dual connectivity with integrated DECT and Bluetooth modes, allowing seamless device switching. Advanced Acoustic Shield 2.0 noise cancellation ensures crystal-clear sound by filtering out background noise. Its ergonomic design provides all-day comfort, and it seamlessly connects with a wide range of IP phones and Unite. Upgrade to the WH64 Headset for the perfect blend of performance, comfort, and connectivity.

KEY FEATURES

- DECT Base & Bluetooth Wireless Connectivity
- Acoustic Shield Technology 2.0
- All-Day-Wearing Comfort
- Visual Base Busylight
- Up to 32 Hours of Talking Time

WH64 BASE PRODUCT SPECIFICATIONS

HOW TO



General

- Port
 - 1 micro USB 2.0 port
 - 1 Type-C USB 2.0 port
 - 1 Mini USB port
 - 1 DC power port
 - 1 busylight port
 - 1 Type-C USB 2.0(on headset)
- Charging stand (for headset)
- USB connectivity to PC and IP phone
- Boom arm adjustable: 280°
- Integrated busylight LED indicator
- WH64 Mono
 - Base:180g
 - Headset: 92 g
- WH64 Dual:
 - Base: 180g
 - Headset: 151 g

Battery

- Talk time:
 - Dect mode: up to 14 hours (Mono), up to 16 hours (Dual)
 - Bluetooth mode: up to 26 hours (Mono), up to 32 hours (Dual)
- Music time:
 - Dect mode: up to 14 hours (Mono), up to 17 hours (Dual)
 - Bluetooth mode: up to 41 hours (Mono), up to 48 hours (Dual)
- Standby time: 157 hours (Mono), 195 hours (Dual)
- Charging time: 1.5 hours (5 V/1.2 A)

DECT

- Wireless range: up to 160 m/525 feet
- Frequency bands:
 - 1880 – 1900 MHz (Europe),
 - 1920 – 1930 MHz (US)
- Secure DECT (level):
 - Step C: authentication
 - DSAA2, encryption
 - DSC2 (128 bit)

Bluetooth

- Bluetooth® device
- Bluetooth version: Bluetooth5.2
- Bluetooth profiles: HFP v1.8, A2DP v1.3.2, AVRCP v1.6.2, SPP v1.2
- Operating range: up to 30m/100 feet

Audio

- Hearing protection: Peak Block protection (EN50332), Australian G616 Protection(AU G616), Daily Noise Exposure Protection
- Microphone type: 3 microphones MEMS
- Speaker size: Φ 30
- Speaker frequency range: 20 Hz-20 kHz
- Talk mode: wideband, 100 Hz-8 kHz, 16 kHz sample rate
- Music mode: 20 Hz-20 kHz, 48 kHz sample rate, Stereo (Stereo only supported by Dual headset)

Call Control

- Answer/End/Reject a call
- Hold/Unhold call
- Volume up/down
- Microphone mute
- Move the microphone boom arm up to mute, or down to unmute

Package Feature

- Package contents:
 - Power adapter
 - Dual or Mono Headset
 - WHB640 Base
 - Drawstring Bag
 - 1* 1.2m USB C to USB A cable
 - 1* 0.8m Micro USB to USB A cable
 - Quick Start Guide
- Optional accessories:
 - Wireless Headset Adapter EHS62
 - Telephone cable for WH64/WH65/WH68
 - Busylight BLT60

QUESTIONS? CONTACT US TODAY!